

Achiever Professional Gas Water Heaters



- More hot water at a low operating cost.
- Exclusive air/fuel shut-off device
- Maintenance free: no filter to clean
- Protective control system that disables the heater in the presence of flammable vapor accumulation.
- Premium grade anode rod provides long-lasting tank protection.
- All models certified up to 5,999 feet above sea level, some certified up to 10,000 feet.
- Easy to light: no matches required
- EverKleen patented system fights sediment build-up
- Exclusive Ruudglass tank lining resists corrosion and prolongs tanks life.
- Enhanced flow brass drain valve.



Pricing

MODEL NUMBER		PROG40-38N RU62	PROG50-38N RU60	PROG40S-38N RU62
TYPE		Tall	Tall	Short
NOMINAL GALLON CAPACITY		40	50	40
RATED GALLON CAPACITY		38	48	39
GAS INPUT IN THOUS. BTU/H	NAT.	38	38	38
	LP	-	-	-
RECOVERY IN G.P.H. 90 F RISE	NAT.	38.4	38.4	38.4
	LP	-	-	-
UEF FIRST HR. DEL. G.P.H.	NAT.	64	85	65
	LP	-	-	-
HEIGHT TO VENT		61.5	61.25	53.25
TANK HEIGHT		58.5	58 3/8	50.25
DIAMETER		19	20.5	21 3/8
HT. TO GAS CONN.		14.25	14.25	14.25
VENT SIZE		3 or 4	3 or 4	3 or 4
WATER CONN. CENTER		8	8	8
HT. TO SIDE T&P VALVE		52.25	51 3/8	44
WATER CONN. SIZE		0.75	0.75	0.75
SHIP WT. (LBS)		127	150	125
UNIFORM ENERGY FACTOR (UEF)		0.58	0.64	0.58
PRICE				