

Achiever Plus Professional Induced Draft Water Heaters



- Well insulated for reduced stand-by heat loss
- 29-Gallon capacity with 87 gallon FHR performance
- Small foot print, 17-3/4 inch diameter
- Integrated self-diagnostic system control for easy installation and service
- Eco-friendly burner, low NOx design
- Exclusive air/fuel shut-off device for double protection
- Protective control system that disables the heater in the presence of flammable vapor accumulation
- EverKleen patented system fights sediment build-up
- Dual certified for both potable water and space heating
- Enhanced flow brass drain valve



Pricing

MODEL NUMBER	PRO+G29-60N RU70 ID
NOMINAL GALLON CAPACITY	29
RATED GALLON CAPACITY	28
GAS INPUT IN THOUS. BTU/H	60
RECOVERY IN G.P.H. 90 F RISE	61
UEF FIRST HR. DEL. G.P.H.	87
EF FIRST HR. DELIVERY G.P.H.	90
HEIGHT TO VENT	65-1/2
TANK HEIGHT	58-1/4
DIAMETER	17-3/4
HT. TO GAS CONN.	14
VENT SIZE	3 or 4
WATER CONN. CENTER	8
HT. TO SIDE T&P VALVE	51-9/16
WATER CONN. SIZE	3/4
SHIP WT. (LBS)	136
ENERGY FACTOR	0.70
UNIFORM ENERGY FACTOR (UEF)	0.71
PRICE	