

Achiever Professional Electric Water Heaters



- Isolated tank design reduces conductive heat loss.
- Resistored copper upper element and resistored Lifeguard stainless steel lower element to prolong anode rod and tank life.
- Exclusive diagnostic system with glowing LEDs that verify heating element operation. LEDs pin point the exact location of functioning or non-functioning heating elements.
- Premium grade anode rod provides long-lasting tank protection.
- Electric junction box located above heating elements for easy installation.
- Over-temperature protector cuts off power in excess temperature situations.
- Automatic thermostat keeps water at desired temperature.
- EverKleen self cleaning device fights harmful sediment build-up with a high-velocity spiraling water stream-helps operating efficiency by saving eneergy, money and improving tank life.
- HUD certified for manufactured housing and modular construction.
- Enhanced flow brass drain valve.



Pricing

MODEL NUMBER	PROE47 S2 RU95	PROE50 T2 RU95
TYPE	Short	Tall
NOMINAL GALLON CAPACITY	47	50
RATED GALLON CAPACITY	43	45
RECOVERY IN G.P.H. 90 F RISE	21	21
UEF FIRST HOUR RATING G.P.H.	54	63
TANK HEIGHT	32	58 5/8
DIAMETER	26 1/4	20 1/4
HEIGHT TO WATER CONN.	34	61 5/8
SHIP WT. (LBS)	149	121
UNIFORM ENERGY FACTOR (UEF)	0.93	0.93
PRICE		