

# Ultra High Efficiency Tankless Water Heaters



## STANDARD FEATURES

- Vent with 2", 3" or 4" PVC
- Built in condensate neutralizer
- Self-diagnostic system for easy installation and service
- EcoNet Enabled: All tankless products from 2010 to present can connect to EcoNet mobile app via Tankless EcoNet Accessory Kit.
- Exclusive Hot Start Programming: Minimizes cold water bursts by staying in ready-fire state for back-to-back hot water needs
- Low Emissions: Ultra low NOx burner meets SCAQMD rule 1146.2 requirements.
- Exclusive Water Savings Setting: Upon activation, this setting can save up to 1,100 gallons water/year by reducing flow at the tap until set temperature is achieved.
- Digital remote control and 10 ft. of thermostat wire included-shows temperature setting and service codes.
- High-altitude capability-up to 8,400 ft. elevation above sea level.
- Industry Best freeze protection to -30F.



## Pricing

Model Number	RUTGH-84DVLN-1	RUTGH-95DVLN-1
GAS INPUT BTU/H	11,000-157,000	11,000-199,900
TYPE	Indoor Direct Vent	Indoor Direct Vent
NUMBER OF BATHROOMS	3	4
TEMP. RANGE	85 to 140 F	85 to 140 F
MIN.FLOW/ACTIVATION GPM	0.26/0.40	0.26/0.40
GPM @ 67 RISE MAX	4.6	5.7
GPM @ 45 RISE MAX	6.7	8.5
MAX GPM	8.4	9.5
CONNECTION	WATER	3/4
	GAS	3/4
HEIGHT	27 1/2	27 1/2
WIDTH	18 1/2	18 1/2
DEPTH	9 3/4	9 3/4
VENT DIAMETER	2", 3" or 4" PVC 2-Pipe	2", 3" or 4" PVC 2-Pipe
SHIP WEIGHT	82	82
UNIFORM ENERGY FACTOR (UEF)	0.96	0.93
PRICE		